

INDOOR CABLE

R - V (Pe) V

PVC Insulated, Single coated aluminium foil shielded,
PVC sheathed

(Specification : STEL-K-010)

Size : 2 up to 100 x 2 x 0.6 mm

DIMENSIONAL DATA

Nominal Conductor diameter	Cable size	Nominal Thickness		Approximately		Standard Length	Delivery form
		Insulation	Sheath	Overall diameter	Net. Weight		
mm	pair	mm	mm	mm	kg/km	m	-
0.6	2	Minimum : 0.15	1.0	5.9	33	250	Coil
	6		1.0	8.4	80	250	
	10		1.0	10.0	115	250	
	20	Nominal : 0.20	1.0	13.0	195	500	Drum
	30		1.3	16.0	293	500	
	40		1.3	17.9	371	500	
	50		1.5	20.2	464	500	
	60		1.5	21.8	541	500	
	70		1.7	23.6	636	500	
	80		1.8	25.1	722	500	
	100		1.8	27.6	868	500	

ELECTRICAL DATA

Nominal Conductor diameter	Resistance at 20 °C		Max . mutual capacitance at 800 Hz	AC Voltage Test
	Max. conductor	Min. insulation		Core to core
mm	Ohm/km	M.ohm.km	nF/km	Volt/1 min
0.6	65	100	120	800

