



Use the QR-tag
to find out more
about AD 10.



Available drill motors- and stands.

	DRILL MOTORS		DRILL STANDS		
	DM 280	DM 340	DS 450	DS 50 GYRO	DS 70 GYRO
Drill diameter, max mm	350	400	450	350	650
Travel, max mm	—	—	700	670	710/ 1190
Weight, incl. carriage, kg	13.0	14.0	24.0	56	83
Read more on page	158	156	166	172	170

Husqvarna DM 340.



Watercooled 3 speed gearbox for optimal drilling performance.



Top with load indicator (LED) for optimal load.

Applications.

- For heavy duty core drilling up to Ø 400 mm together with Husqvarna drill stands.
- For a variety of materials, including reinforced concrete, brick and other building materials.
- Heavy-duty applications like water evacuation, ventilation and plumbing channels, waste evacuation pipes, gas supply pipes, barriers, road signs and holes in corners for wall sawing openings.
- For angle drilling, stitch drilling and drilling in all directions, with Husqvarna drill stands.

Benefits.

- Equipped with Elgard™ which indicates via the LED if the machine is overloaded. This means the operator can always drill at maximum pressure, preventing motor damage and extending product life.
- Pressing the SmartStart™ button reduces start speed by 50 %.

- SoftStart™ – electronic current limiter means full speed is reached about two seconds after start.
- Ergonomically designed handle for easier transport and faster set-up.
- The controls are designed and positioned to enhance ergonomics and facilitate operation.
- The water hose can turn 180, for greater flexibility in terms of setup configuration.

Technical specifications.

Power	3300 W
1-phase rated voltage	230 V
Spindle speed full load	170 / 380 / 650 rpm
Spindle thread	1 1 / 4" 7 UNC
Rec. drill diameter, max	400 mm
Weight	14.0 kg

More technical specifications on page 180.

Product specifications.

DM 340, 230 V	965 98 72-07
---------------	--------------

Diamond drill bits.

MATERIAL	D 1200 DIAGRIP™ SERIES					D 800 SERIES		
	D 1210	D 1220	D 1235	D 1245	D 1265	D 820	D 845	D 865
NATURAL STONE, GRANITE / SANDSTONE	● ● ●	●	●	—	—	●	—	—
CONCRETE, HARD	● ● ●	● ● ●	● ●	—	—	● ● ●	—	—
CONCRETE, MEDIUM	● ●	● ● ●	● ● ●	● ●	●	● ● ●	●	●
CONCRETE, SOFT	●	● ●	● ● ●	● ● ●	● ● ●	● ●	● ● ●	● ● ●
CONCRETE, ABRASIVE	●	●	● ●	● ●	● ● ●	●	● ● ●	● ● ●
ASPHALT	—	—	—	—	● ● ●	—	—	● ● ●
BRICK	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
CEMENT BLOCKS	● ●	● ●	● ● ●	● ●	● ●	● ●	● ●	● ●
Read more on page	186	186	186	186	186	192	192	192

● ● ● = Optimal ● ● = Good ● = Acceptable — = Not recommended



A large selection of slurry collectors.




V-shaped slurry collectors.



U-shaped slurry collectors.



Drill snap makes it easy to knock the drill out of the hole.



Anchoring kit, incl large nut, holding screw, pointer and 5 anchors.



Anchoring systems, for anchoring in abrasive materials.



Washer quick release, to release the drill motor thread from the drill bit.



Pressurised water tank holds 15 litres and comes with a 3-meter hose.



WT 15 - battery-powered water tank.



Large selection of adapters to suit various threads.



Extensions, for deep drilling with standard drill bits.



The AD 10 is a unique automatic drill system.



DC 1400 is an efficient, compact, single-phase dust collection unit.

Accessories.

A	Slurry collector, 160 mm	531 28 00-02
A	Slurry collector, 180 mm	531 28 02-96
A	Slurry collector, 210 mm	531 28 00-03
A	Slurry collector, 220 mm	531 07 46-82
A	Slurry collector, 260 mm	531 28 00-04
A	Slurry collector, 310 mm	531 28 00-05
B	Slurry collector V-shaped, 350 mm	531 07 46-22
B	Slurry collector V-shaped, 700 mm	531 28 00-07
C	Slurry collector U-shaped, 212 mm	531 28 03-29
D	Drill snap, CR 128	531 07 20-03
D	Drill snap, 1 1/4"	531 07 46-74
E	Anchoring kit	502 43 48-01
E	Anchors	502 43 54-01

F	Anchoring system, 1 m	502 43 49-01
F	Anchoring system, 1.5 m	502 43 50-01
G	Washer quick release	543 03 91-82
H	Pressurised water tank	506 32 63-02
I	Water pump, WT 15, 230 V	965 97 10-01
I	Water pump, WT 15, 110 V	965 97 10-02
J	Adapter drill bit*, 1 1/4" F – 1/2" G F	543 04 64-26
J	Adapter drill bit*, 1 1/4" F – CR 128 M	531 07 20-02
K	Extension drill bit*, 300 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-02
K	Extension drill bit*, 500 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-04
K	Extension drill bit*, 1000 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-05
L	AD 10	966 66 66-01
M	DC 1400	966 76 68-01

*See page 201 for more drill bit accessories.

Available drill stands.

	RECOMMENDED				
	DS 450	DS 70 GYRO	DS 70 ATS	DS 70 AT	DS 50 GYRO
Drill diameter, max mm	450	650	650	450	350
Travel, max mm	700	710/1190	680	680	670
Weight, incl. carriage, kg	24.0	83	37	32	56
Read more on page	166	170	174	175	172

Husqvarna DM 280.



Watercooled 3 speed gearbox
for optimal drilling performance.



Use the QR-tag to find out
more about DM 280.

Applications.

- For medium core drilling up to Ø 350 mm together with Husqvarna drill stands.
- For a variety of materials, including reinforced concrete, brick and other building materials.
- Medium applications like water evacuation, ventilation and plumbing channels, waste evacuation pipes, gas supply pipes, barriers, road signs and holes in corners for wall sawing openings.
- For angle drilling, stitch drilling and drilling in all directions, with Husqvarna drill stands.

Benefits.

- Equipped with Elgard™ which indicates via the LED if the machine is overloaded. This means the operator can always drill at maximum pressure, preventing motor damage and extending product life.
- Pressing the SmartStart™ button reduces start speed by 50 %.
- SoftStart™ – electronic current limiter means full speed is reached about two seconds after start.

- Ergonomically designed handle for easier transport and faster set-up.
- The controls are designed and positioned to enhance ergonomics and facilitate operation.
- The water hose can turn 180°, for greater flexibility in terms of setup configuration.

Technical specifications.

Power	2700 W
1-phase rated voltage	230/110 V
Spindle speed full load, high speed version	350/780/1340 rpm
Spindle speed full load, low speed version	240/540/930 rpm
Spindle thread	1 1/4" 7 UNC
Rec. drill diameter, max	250/350 mm
Weight	13.0 kg

More technical specifications on page 180.

Product specifications.

HIGH SPEED VERSION	
DM 280, 230 V, high speed	966 55 41-06
LOW SPEED VERSION	
DM 280, 230 V, low speed	966 55 41-01

Diamond drill bits.

MATERIAL	D 1200 DIAGRIP™ SERIES					D 800 SERIES		D 400 SERIES	
	D 1210	D 1220	D 1235	D 1245	D 1265	D 820	D 865	D 420	D 465
NATURAL STONE, GRANITE / SANDSTONE	●●●	●	●	—	—	●	—	●	—
CONCRETE, HARD	●●●	●●●	●●	—	—	●●●	—	●●●	—
CONCRETE, MEDIUM	●●	●●●	●●●	●●	●	●●●	●	●●●	●
CONCRETE, SOFT	●	●●	●●●	●●●	●●●	●●	●●●	●●	●●●
CONCRETE, ABRASIVE	●	●	●●	●●	●●●	●	●●●	●	●●●
ASPHALT	—	—	—	—	●●●	—	●●●	—	●●●
BRICK	●●	●●	●●	●●	●●	●●	●●	●●	●●
CEMENT BLOCKS	●●	●●	●●●	●●	●●	●●	●●	●●	●●
Read more on page	186	186	186	186	186	192	192	200	200

●●● = Optimal ●● = Good ● = Acceptable — = Not recommended



A large selection of slurry collectors.




V-shaped slurry collectors.




U-shaped slurry collectors.



Drill snap makes it easy to knock the drill out of the hole.



Anchoring kit, incl large nut, holding screw, pointer and 5 anchors.



Anchoring systems, for anchoring in abrasive materials.



Washer quick release, to release the drill motor thread from the drill bit.



Pressurised water tank holds 15 litres and comes with a 3-meter hose.



WT 15 - battery-powered water tank.



Large selection of adapters to suit various threads.



Extensions, for deep drilling with standard drill bits.



The AD 10 is a unique automatic drill system.



DC 1400 is an efficient, compact, single-phase dust collection unit.

Accessories.

A	Slurry collector, 160 mm	531 28 00-02
A	Slurry collector, 180 mm	531 28 02-96
A	Slurry collector, 210 mm	531 28 00-03
A	Slurry collector, 220 mm	531 07 46-82
A	Slurry collector, 260 mm	531 28 00-04
A	Slurry collector, 310 mm	531 28 00-05
B	Slurry collector V-shaped, 350 mm	531 07 46-22
B	Slurry collector V-shaped, 700 mm	531 28 00-07
C	Slurry collector U-shaped, 212 mm	531 28 03-29
D	Drill snap, CR 128	531 07 20-03
D	Drill snap, 1 1/4"	531 07 46-74
E	Anchoring kit	502 43 48-01
E	Anchors	502 43 54-01

F	Anchoring system, 1 m	502 43 49-01
F	Anchoring system, 1.5 m	502 43 50-01
G	Washer quick release	543 03 91-82
H	Pressurised water tank	506 32 63-02
I	Water pump, WT 15, 230 V	965 97 10-01
I	Water pump, WT 15, 110 V	965 97 10-02
J	Adapter drill bit*, 1 1/4" F – 1/2" G F	543 04 64-26
J	Adapter drill bit*, 1 1/4" F – CR 128 M	531 07 20-02
K	Extension drill bit*, 300 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-02
K	Extension drill bit*, 500 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-04
K	Extension drill bit*, 1000 mm, 1 1/4" F – 1 1/4" M, steel	543 04 65-05
L	AD 10	966 66 66-01
M	DC 1400	966 76 68-01

*See page 201 for more drill bit accessories.

Available drill stands.

	RECOMMENDED				
	DS 450	DS 70 ATS	DS 70 AT	DS 50 GYRO	DS 250
Drill diameter, max mm	450	650	450	350	250
Travel, max mm	700	680	680	670	685
Weight, incl. carriage, kg	24.0	37	32	56	16.0
Read more on page	166	174	175	172	168